



H.F.ELECTRONICWELDING

Af 5040 Ro is a High Frequency sealing press available in 3 models.

Technical features

* with blade between 1.5 and 2 mm

| model | 5040 | 5040 AUTOM | 5585 |
|---------------------------|--------------------|--------------------|--------------------|
| voltage (power supply) | 380 v - n/t 50hz | 380 v - n/t 50hz | 380 v - n/t 50hz |
| max. absorbed power | 14 kva | 14 kva | 14 kva |
| max. delivered power | 9 wk | 9 wk | 9 wk |
| sealing power* | 6 m | 6 m | 6 m |
| work frequency | 27,12 mhz | 27,12 mhz | 27,12 mhz |
| work surfaces | 2 | 3 | 2 |
| max. work surface dim. | 500 x 400 mm | 500 x 400 mm | 850 x 550 mm |
| plate rotation | manual | automatic | automatic |
| electrode max. height | 110 mm | 110 mm | 110 mm |
| blister valve max. height | 100 + 100 mm | 100 + 100 mm | 100 + 100 mm |
| air pressure | 6 bar | 6 bar | 6 bar |
| press closing power | 1.000 kg a 6 bar | 1.000 kg a 6 bar | 1.000 kg a 6 bar |
| max. plate temperature | 140° c | 140° c | 140° c |
| dimensions (h x w x d) | 180 x 100 x 200 cm | 240 x 200 x 270 cm | 240 x 210 x 270 cm |
| weight | 700 kg | 1.000 kg | 1.000 kg |